

DT125



Its maintenance simplicity does the difference because no ground conditions can terrify the 2-stroke engine and the monocross suspension of the DT125. Easy to repair, and cheap to maintain, this is one of the references of the governments, NGOs, and companies.



Colors
available



MOTOR

| | |
|----------------------------|---------------------------|
| Engine type | Single cylinder, 2-stroke |
| Displacement (cc) | 125 |
| Cooling system | Air-cooled |
| Compression ratio | 7,2 : 1 |
| Maximum power (hp / rpm) | 15 / 7000 |
| Maximum torque (N.m / rpm) | 15,2 / 6500 |
| Starter system | Kick starter |
| Lubrication system | Autolube |
| Ignition system | CDI |
| Fuel delivery | Carburetor |



CHASSIS

| | |
|-------------------------|----------------------|
| Frame | Double steel cradle |
| Front suspension system | Telescopic fork |
| Rear suspension system | Swingarm (monocross) |
| Front brake | Drum |
| Rear brake | Drum |
| Wheels | Spoke |
| Front tyre | 2,75-21 4PR |
| Rear tyre | 4,10-18 4PR |



DIMENSIONS

| | |
|------------------------------|---------------|
| Overall dim - L x w x h (mm) | 2110*865*1165 |
| Wheelbase (mm) | 1340 |
| Seat height (mm) | 830 |
| Min ground clearance (mm) | 260 |



TRANSMISSION

| | |
|---------------------|---------|
| Transmission system | 6-speed |
|---------------------|---------|



WEIGHT/CAPACITIES

| | |
|------------------------|------|
| Dry weight (kg) | 98 |
| Fuel tank capacity (L) | 9,50 |



EQUIPMENTS



Luggage
Pack

Kick
starter

Spoke
wheels

THE rules

1 Always wear a helmet, eye protection and protective proper clothing.

For more information, please contact your dealer YAMAHA.

2 YAMAHA encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

